



LASER Marking System (LM100)

The OCS LASER Marking System is designed and manufactured using state-of-the-art technology. The LM100 can be used to mark or label defects on polymer films (tape). The labelling and marking settings as well as the power of the laser can be configured with the operator software to the corresponding product requirements. The LASER Marking System consists of laser, control and suction unit.

The laser unit essentially consists of a class 4 air-cooled laser, a two-part protective cover, a viewing window and a pneumatically swivelling film guide. The laser unit has two air filters so that neither dirt nor dust accumulates inside its CO2 laser.

Markable Materials

Polymer films (tape)

Features

- Laser unit with class 4 air-cooled CO2 laser
- Two-part protective cover completely encloses the danger area
- $\bullet\,$ Two air filters prevent dirt and dust from accumulating in the laser unit
- LED lighting
- Pneumatically swivelling film guide
- Adjustable movement speed of the swivel arms
- Viewing window on the laser unit
- Operator software with a wide range of labelling and marking settings

Sales Team



T +49 2302 95622-0 F +49 2302 95622-33 info@ocsgmbh.com www.ocsgmbh.com

Address

OCS Optical Control Systems GmbH Wullener Feld 24 58454 Witten Germany



Compatible with

- OCS Tape Line
- OCS Modular Film Analyser (MFA)

Technical Details

Wavelength of the laser

10.6 μm

More Product Pictures







Similar Products



Modular Film Analyser (MFA)

The OCS Modular Film Analyser (MFA) is used for the continuous cooling, stripping and winding of extruded polymer film. In combination with a variety of different measuring instruments, a wide range of applications for the analysis of different sample materials is covered. In addition to the Film Surface Analyser (FSA100V2/FSA200V2) for optical quality control of the polymer film, online spectroscopy, the measurement of haze and transmission as well as gloss and thickness can be integrated. This allows the combination of a tailor-made and yet economical solution. [vc column width="1/22"] Features Modular architecture for customer-specific configuration with different measurement devices Homogeneous, ... [read more on our Website]



Label Printer (LP100)

The OCS Label Printer (LP100) ensures the highest quality standards with regard to the labelling of, and repair of defects on, polymer films. Simple operation enables reliable and fast printing. [vc_column width="1/2\mathbb{Z}] Labelable Materials Polymer films (tape) [vc_column width="1/2\mathbb{Z}] Features Reliable and fast printing Precise impression Easy operation Compact design Meets the highest quality standards Compatible with OCS Tape Line OCS Modular Film Analyser (MFA) ... [read more on our Website]



Tape Line (TCA®)

The OCS Tape Line Type TCA® is used for testing transparent polymer films (tape). It consists of the OCS Measuring Extruder (ME) and the OCS Modular Film Analyser with Calender (MFA-Calender). Our calendaring system has been specially developed for the wire and cable industry. It presses and cools the extruded polymer film (tape) from both sides, thus ensuring a smooth and consistent surface thickness for optical anlysis. The Tape Quality Analyser (TQA100) contains a highresolution camera system that detects contaminants, gels, black specks, fibres and metal particles. The detected errors are marked by the LASER Marking System (LM100) or ... [read more on our Website]



Tape Line (SSA®)

The OCS Tape Line type SSA® is used specifically to detect surface irregularities (pips) on non-transparent polymer films (tape) in the wire and cable industry. The SSA® Line consists of a Measuring Extruder (ME) and a Modular Film Analyser with a Chill Roll (MFA-CR). During the measurement of the surfaces, the extruded polymer film (tape) passes over a chill roll, which leads the tape to the Surface Quality Analyser (SQA). This high-resolution CMOS camera system uses a specially developed measuring roll to measure the height of the surface defects (so-called pips or agglomerates) with a resolution of 1 ... [read more on our Website]



Film Cutter and Sorter (OFC100)

The OCS Film Cutter and Sorter (OFC100) performs two tasks in one system. First, it continuously shreds the polymer film into sections of consistant length (specified value) and ejects them. The ejected film cuttings are then collected in a collection container. The OFC100 automatically sorts out the marked and contaminated film sections with the help of the software. These marked sections are significantly longer for purposes of further analysis and are ejected separately via the sorting ejector into another collection container. Here, too, the length of the marked film sections can be defined. [vc column width="1/2?] Cuttable and Sortable Materials ... [read more on our Website]



Images, drawings and data are non-binding and subject to modification without prior notice. © 2025. All rights reserved - OCS Optical Control Systems GmbH | Wullener Feld 24 | 58454 Witten, Germany